

LUBRI-F6

MULTIPURPOSE
HIGH PERFORMANCE LUBRICANT



- Automotive Industry
- Civil Construction
- Institutional
- Agriculture and Livestock
- Cleaning and Maintenance
- Hotels and Restaurants
- Environment
- Industry

PROPERTIES

LUBRI-F6 is a neutral product, colourless, non-irritating, UV resistant and with a pleasant pine odour.

Contains no silicone or chlorinated solvents. LUBRI-F6 is an excellent multipurpose lubricant that through its low surface tension penetrates easily in incrustated oxides.

The anti-moisture characteristics of LUBRI-F6 make possible its application in extreme conditions.

Can be used in emergencies to prevent humidity or applied in a preventive way.

LUBRI-F6 has a dielectric capacity of 63 000 Volt tested according to IEC 156 Standard.

UTILIZATION

LUBRI-F6 has an excellent performance to loosen metal pieces blocked by corrosion or oxidation, such as nuts, screws, bolts, hinges, joints, rails, joints, axles and other calcined mechanisms.

Eliminates charred dirt and heavy and light hydrocarbons. It is compatible with all types of plastics, rubbers and does not attack paintings. When applied to metals, leaves a anticorrosion film.

LUBRI-F6 is also used in all lubrication applications.

Can be used in tools, machines, rails, hinges, etc., as well as in all kinds of places where the micro-lubrication is essential.

Lubri-F6 is an excellent multipurpose product for all types of industrial maintenance tasks.

ADVANTAGES

- High performance
- Aerosol of new generation
- Innovative propellant gas
- Multiposition
- Low surface tension

6 Functions:

- Lubricant
- Unblock
- Deoxidising
- Protective anti-corrosion
- Degreaser
- Anti-humidity dielectric



LUBRI-F6 application example

TECHNICAL SPECIFICATIONS	
DILUTION	Not applicable
CHEMICAL NATURE	Preparation based on lubricants and anti-corrosion additives, with penetrating functions.
SURFACTANTS	Not applicable
PHYSICAL STATE / COLOUR	Liquid of amber colour
ODOUR	Similar to oil
pH	Not concerned
SOLUBILITY IN WATER	Insoluble
CLEANING PERFORMANCE	Not applicable
RINSING	Not applicable
FOAMING	Not applicable
RELATIVE DENSITY	0,830
FLASH POINT	64 °C
CHEMICAL REACTION	Not applicable
CLASSIFICATION	Extremely flammable
EXPIRATION	2 years. Stored in the original packaging. Protect from excessive sunlight. Avoid extreme temperatures.



CAUTIONS

Chemical product: Always read the label and Safety Data Sheet before using. Keep out of children reach. Avoid contact with eyes. Contents under pressure, do not expose to temperatures exceeding 50°C. Do not puncture or incinerate even when empty. Do not spray on incandescent material.

Always make a test to determine the compatibility and the appropriate contact time.

APPLICATION MODE
Shake well before using. Spray in calcined pieces, let soak a few seconds for that penetration be effective. Repeat if needed.



PORTUGAL

Imporquímica - Indústria Portuguesa de Produção Química, S.A.
Zona Industrial Alto do Carvalhinho, Lote 11 - Apartado 39
2861-909 Moita - Portugal
Tel: +351 212 808 390 | Fax: +351 212 808 395
E-mail: info@imporquimica.pt

ANGOLA

Imporquímica Angola, SA
Estrada do Zango/Viana Polo Industrial Tubogás
Armazéns 35 e 36 - Município de Viana, Luanda Angola
Tel.: +244 222 290 850 | Fax: +244 222 290 230
E-mail: angola@imporquimica.com

CAPE VERDE

Imporquímica Cabo Verde, Lda.
Armazém Achada Grande de Trás
Ilha de Santiago, Praia - Cabo Verde
Tel.: +238 939 07 48
E-mail: caboverde@imporquimica.com

MOZAMBIQUE

Imporquímica Moçambique, Lda.
Avenida Zedequias Manganhela, n.º 267, Prédio JAT IV
4º andar, Maputo - Moçambique
Tel.: +258 845 797 467
E-mail: mocambique@imporquimica.com

NIGERIA

Imporquímica Nigeria Chemicals, Ltd.
Plot 59 Trans Amadi Industrial Layout,
Port Harcourt, Rivers State, Nigeria
Tel: +234 (0) 84 556 004
E-mail: info@nigeria-chemicals.com



visit us
IMPORQUIMICA.COM

LUBRI-F6